

Numerical Simulation of Dynamic Systems: Hw2 - Problem

Prof. Dr. François E. Cellier
Department of Computer Science
ETH Zurich

March 5, 2013

[H2.1] Marginal Stability

Given the following linear time-invariant continuous-time system:

$$\dot{\mathbf{x}} = \begin{pmatrix} 1250 & -25113 & -60050 & -42647 & -23999 \\ 500 & -10068 & -24057 & -17092 & -9613 \\ 250 & -5060 & -12079 & -8586 & -4826 \\ -750 & 15101 & 36086 & 25637 & 14420 \\ 250 & -4963 & -11896 & -8438 & -4756 \end{pmatrix} \cdot \mathbf{x} + \begin{pmatrix} 5 \\ 2 \\ 1 \\ -3 \\ 1 \end{pmatrix} \cdot u$$
$$\mathbf{y} = \begin{pmatrix} -1 & 26 & 59 & 43 & 23 \end{pmatrix} \cdot \mathbf{x}$$

with initial conditions:

$$\mathbf{x}_0 = \begin{pmatrix} 1 \\ -2 \\ 3 \\ -4 \\ 5 \end{pmatrix}$$

[H2.1] Marginal Stability II

Determine the step size, h_{marg} , for which FE will give marginally stable results.

Simulate the system across **10 seconds** of simulated time with step input using the FE algorithm with the following step sizes:

1. $h = 0.1 \cdot h_{\text{marg}}$,
2. $h = 0.95 \cdot h_{\text{marg}}$,
3. $h = h_{\text{marg}}$,
4. $h = 1.05 \cdot h_{\text{marg}}$, and
5. $h = 2 \cdot h_{\text{marg}}$.

Discuss the results.

[H2.5] Stability Domain

For the *predictor-corrector FE-BE method*, find the stability domains if:

1. no corrector is used,
2. one corrector is used,
3. two correctors are used,
4. three correctors are used, and
5. four correctors are used.

Plot the five stability domains on top of each other, and discuss the results.